

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1 to 39 (Cancelled)

Claim 40. (Currently Amended) The security combination for a doorway comprising:

a door frame constructed in an opening of a wall and having two vertical sides,

a door jamb attached vertically to and extending the length of one vertical side of the door frame, the door jamb having at least one opening to receive a locking member,

a door sized and shaped to fit within the door frame, the door having a front surface, a rear surface, a top surface, a bottom surface, a free vertical edge portion, and a hinged vertical edge portion, the free vertical edge portion comprising at least one lockset having a portion protruding through the front surface of the door and having a locking member,

a first U-shaped reinforcing member capable of being securely affixed to the free vertical edge portion of the door, said reinforcing member comprising a ~~metal~~rigid material, extending substantially along the full length of the free vertical edge portion of the door, having at least one opening for passage of the locking member from the at least one lockset having a locking member, and comprising a base member and two substantially perpendicularly positioned side members, each of the side members being generally rectangular and extending substantially along the free vertical edge portion of the door and having a proximal edge connected to the base member and a distal edge, the distal edge ~~located between the proximal edge and~~ not extending beyond the portion of the

lockset protruding through the front surface of the door and a substantially planar surface, and

a second reinforcing member capable of being securely affixed to the door jamb, said second reinforcing member having at least one opening for passage of the locking member from at least one lockset having a locking member,

wherein the U-shaped reinforcing member is over-bend mounted to the free vertical edge portion of the door so that the reinforcing member engages the free vertical edge portion of the door without being screwed to the free vertical edge portion of the door, wherein the second reinforcing member has a length of from about 12 inches to substantially the length of a vertical portion of the door, and wherein force applied against the front or rear surface of the door will be transmitted through at least one locking member to the second reinforcing member and to the door frame.

Claim 41. (Previously Presented) The security combination of Claim 40, wherein the at least one lockset is a deadbolt locking set and the locking member is a deadbolt.

Claim 42. (Previously Presented) The security combination of Claim 41, wherein the at least one lockset is a door latch set and the locking member is a door latch.

Claim 43. (Previously Presented) The security combination of Claim 40, wherein first and second reinforcing members are each comprised of metal.

Claim 44. (Previously Presented) The security combination of Claim 43, wherein the metal is cold-rolled steel, stainless steel, or brass.

Claim 45. (Previously Presented) The security combination of Claim 40, wherein the U-shaped first reinforcing member is further affixed to the first portion of the door by adhesive.

Claim 46. (Previously Presented) The security combination of Claim 45, wherein the adhesive is silicon adhesive.

Claim 47. (Cancelled).

Claim 48. (Previously Presented) The security combination of Claim 40, wherein the second reinforcing member has a tubular member to receive a locking member.

Claim 49. (Previously Presented) The security combination of Claim 40, wherein the door is a metal door.

Claims 50 to 51 (Cancelled)